

TECHNICAL DATA SHEET

Wall Switch 2

FAGERHULT

Art. no: 86284



Organic Response Wall Switch 2 (6 button)

The Organic Response Wireless Wall Switch allows users to manually override the automatic operation of Organic Response enabled luminaires with the push of a button - as detailed in the table below.

BUTTON	OPERATION
On/Auto	Light revert back to Organic Response operating mode
Off	Turn lights off (0 % light level)
Dim -	Dim lights down by one dimming level from current
Dim +	Dim lights up by one dimming level from current
Scene A	Set lights to Scene A light output
Scene B	Set lights to Scene B light output
Indicator LED	Flashes to acknowledge each button press

TECHNICAL DETAILS	
DIMENSIONS	H: 116mm x L: 76mm x W: 19mm
WEIGHT	130g
SCENE CUSTOMISATION	Via Organic Response App & IR Dongle
POWER	Battery, 4 x AAA (Alkaline)
COMMUNICATION	Wireless Infrared
EXPECTED BATTERY LIFE	5 years @ 20 button presses / day
MOUNTING	Double-sided tape or screw to standard mounting plate
DEFAULT SCENE LIGHT LEVELS	Scene A: 50 % Scene B: 100 %
SCENE CUSTOMISATION	Via handheld remote
EMC COMPLIANCE	EN 61000-6-3:2007 + A1:2011 EN 61000-6-2:2005 CFR47 FCC Part 15B, Subpart B (Class B)
COMPLIES WITH EC DIRECTIVES	EMC Directive 2014/30/EU RoHS2 Directive 2011/65/EU
PACKAGING	Dimensions: H: 29mm x L: 123mm x W: 85mm Weight: 160g Quantity: 1