

PLEIAD G4



Pleiad G4 Flex

Pleiad G4 70

Pleiad G4 125

Pleiad G4 165

Pleiad G4 205

Pleiad G4 Wallwasher

Pleiad G4 Robust

Pleiad G4 Surface 128

Pleiad G4 Surface 168

Cut out dimensions (mm)	110	70	125	165	205	165	205	128	168
Ceiling thickness	5-50	5-50	5-50	5-50	5-50	0-35			
Max height	110	104	98	98	107	138	125	134	154
Low Lumen (LL)	790-829	790-830	1200	1300	1675	900	1100	1000	1600
Medium Lumen (ML)				1800		1700	1600	1400	2500
High Lumen (HL)	1400	1400	2350	2800	2800	2500	2600	2400	4500
Extra High Lumen (EHL)				3700	5400				
Narrow Beam ~ 20°	●	●							
Medium Beam 40-50°	●	●	●	●	●			●	●
Wide Beam >70°			●	●	●		●	●	●
< UGR 19		●	●	●	●		●	●	●
< 3000 cd/m²		●	●	●	●		●	●	●
Specular reflector						●			
Matt reflector		●	●	●	●	●	●	●	●
White reflector		●	●	●	●			●	●
Black reflector	●	●	●	●	●			●	●
2700 K / CRI 98 /SDCM 2		●							
3000 K	●	●	●	●	●	●	●	●	●
4000 K	●	●	●	●	●	●	●	●	●
CRI >80	●	●	●	●	●	●	●	●	●
CRI >90	●	●	●	●	●	●	●	●	●
SDCM 3	●	●	●	●	●	●	●	●	●
On/Off Standard	●	●	●	●	●	●	●	●	●
DALI/Phase-pulse	●	●	●	●	●	●	●	●	●
CLO	●	●	●	●	●	●	●		●
	Tilt 45° Turn 355°			Tunable White RGB/W Emergency	Tunable White Emergency	Tunable White RGB/W Emergency			Tunable White