

PLEIAD G4

									
	Pleiad G4 Flex	Pleiad G4 70	Pleiad G4 125	Pleiad G4 165	Pleiad G4 205	Pleiad G4 Wallwasher	Pleiad G4 Robust	Pleiad G4 Ytmonterad 128	Pleiad G4 Ytmonterad 168
Håltagningsmått (mm)	110	70	125	165	205	165	205	128	168
Taktjocklek	5-50	5-50	5-50	5-50	5-50	0-35			
Max höjd	110	104	98	98	107	138	125	134	154
Low Lumen (LL)	790-829	790-830	1200	1300	1675	900	1100	1000	1600
Medium Lumen (ML)				1800		1700	1600	1400	2500
High Lumen (HL)	1400	1400	2350	2800	2800	2500	2600	2400	4500
Extra High Lumen (EHL)				3700	5400				
Smalstrålande~ 20°	●	●							
Medelstrålande 40-50°	●	●	●	●	●			●	●
Bredstrålande >70°			●	●	●		●	●	●
< UGR 19		●	●	●	●		●	●	●
< 3000 cd/m²		●	●	●	●		●	●	●
Blank reflektor						●			
Matt reflektor		●	●	●	●	●	●	●	●
Vit reflektor		●	●	●	●			●	●
Svart reflektor	●	●	●	●	●			●	●
2700 K / CRI 98 /SDCM 2		●							
3000 K	●	●	●	●	●	●	●	●	●
4000 K	●	●	●	●	●	●	●	●	●
CRI >80	●	●	●	●	●	●	●	●	●
CRI >90	●	●	●	●	●	●	●	●	●
SDCM 3	●	●	●	●	●	●	●	●	●
On/Off Standard	●	●	●	●	●	●	●	●	●
DALI/faspuls	●	●	●	●	●	●	●	●	●
CLO	●	●	●	●	●	●	●		●
	Tilt 45° Turn 355°			Tunable White RGB/W Nödljus	Tunable White Nödljus	Tunable White RGB/W Nödljus			Tunable White